

**ULTRA SHORT-THROW
INTERACTIVE PROJECTORS
EB-1400Wi/EB-1410Wi**

EPSON
EXCEED YOUR VISION


**SUPERIOR ULTRA SHORT-THROW
PROJECTORS WITH ENHANCED
INTERACTIVE FEATURES.**



The Epson ultra short-throw projectors EB-1400Wi and EB-1410Wi come with brilliant interactive features like split screen projection and dual on-screen pens for simultaneous writing, and efficient hands-on brainstorming sessions and group meetings. Now you can apply live annotations to your presentation and print them wirelessly, with or without a PC.



EB-1400Wi/EB-1410Wi



Wi-Fi Dual Interactive Pens Ultra Short Throw Split Screen 10W Speaker iProjection

ENGINEERED FOR BUSINESS

Ultra Short-Throw for Better Presentations

With Epson's ultra-short throw advantage to deliver uninterrupted presentations with minimal shadow interference and glare.

Brilliant Interactive Functions

The instant annotation tool, two interactive pens and auto calibration feature deliver interactive presentations easily.

Flexible Projection Modes

Create an interactive environment using any surface like whiteboards, walls and even tabletops.



MODEL NUMBER		EB-1400Wi	EB-1410Wi	
Projection Technology		RGB liquid crystal shutter projection system (3LCD)		
Specification of Main Parts				
LCD	Size	0.59" with MLA		
	Native Resolution	WXGA		
	Projection Lens	Type	No Optical Zoom / Focus (Manual)	
		F-Number	1.80	
		Focal Length	3.71mm	
Lamp	Zoom Ratio	1-1.35 (Digital Zoom)		
	Throw Ratio	0.27 - 0.37 (Wide - Tele)		
	Type	190W UHE	215W UHE	
	Life (Normal/Eco)*1	3,500 / 5,000 hours		
Screen Size (Projected Distance)		74.3" screen 0.438m, 60" to 100" [0.348 to 0.597m]		
Brightness**2				
White Light Output (Normal/Eco)	2,600lm / 1,800lm	3,100lm / 1,800lm		
Colour Light Output	2,600lm	3,100lm		
Contrast Ratio		3,000:1		
Internal Speaker(s)		10W (Monaural)		
Keystone Correction		±3° / ±3°		
Connectivity				
Analog Input	D-sub 15pin	1 (Blue)		
	Component	D-sub 15pin (Blue-molding) x 1 (in common with Analog RGB connector)		
	Composite	RCA x 1 (Yellow)		
Digital Input	HDMI	1 (HDCP supported)		
	Display Port	1		
Output Terminal	D-sub 15pin	1 (Black)		
Audio Input	Stereo Mini Jack	3		
Audio Output	Stereo Mini Jack	1		
Others	USB Type A	2 (USB Memory / ELPDC06 Document Camera)		
	USB Type B	1 (USB Display, mouse, K/B, Interactive)		
Control I/O	RS-232C	D-sub 9pin x 1		
	Remote Control Input	1 (Control Pad Power Source)		
Network	Wired LAN	RJ45 x 1 (10/100Mbps)		
	Wireless	Yes (ELPAP07)		
Operating Temperature		5°C to 35°C <41°F to 95°F> (20% - 80% humidity, unfrozen)		
Operating Altitude		0m to 2,286m <0ft to 7,500ft> (over 1,500m / 4,921ft: with High altitude mode)		
Direct Power On / Off		Yes / No		
Start-Up Period		About 8 seconds, Warm-up period: 30 seconds		
Cool Down Period		Instant off		
Air Filter	Type	High Efficiency Filter		
	Maintenance Cycle	5,000H*3		
Power Supply Voltage		100 - 240 V AC ±10%, 50/60 Hz		
Power Consumption (220-240V)				
Lamp On (Normal / Eco)	281W / 222W	307W / 222W		
Standby (Network On / Off)	5.0W / 0.27W	5.0W / 0.27W		
Dimension Exclude Feet (W x H x D)		367mm x 155mm x 375mm		
Weight		5.6 kg (without SlidePlate), 6.3 kg (with SlidePlate)		
Fan Noise (Normal / Eco)		35 dB / 28dB		
Interactive Specification				
Basic Specification	Technology	Infrared		
	Input Devices	Digital Pen (Easy Interactive Pen 1 and 2)		
	Connection to PC	USB, Network		
	Calibration	Auto / Manual (25points)		
Computer Interactive	Functions	Hover, Right click, Auto Adjust Pen Area		
	Driver Installation	Windows, Linux*4: No Installation required Mac OS X: Installation required.		
	Multi-Pen Support	Yes (with Easy Interactive Tools Ver.2.10). Up to 2 types of pens. (Easy Interactive Pen 1 and 2)		
Instant Annotation (Pc-Less)	Multi-Pen Support	Yes. Up to 2 types of pens. (Easy Interactive Pen 1 and 2)		
Whiteboard Mode	Multi-Pen Support	Yes. Up to 2 types of pens. (Easy Interactive Pen 1 and 2)		
	Whiteboard Function	Yes		
	Functions	Multi-Page support, Power-Off recovery, template, Capture function, Export Meeting, Printer & Scanner support		
External Control Pad Specification				
Dimension	Exclude Protrusion (W X H X D)	136mm x 149mm x 29mm		
Weight		240g (Excluding Batteries and Rubber feet)		
Battery Life		Condition: 250 days/year, 100 times/day, 0.5 s/time		
		Alkaline dry cell: 2.8years		
		Manganese dry cell: 0.6year		
Interface(s)	USB Type-A (User Input)	2 (USB memory / Printer)		
	USB Type-B (User Input)	1 (PC-Interactive / USB Display)		
	Stereo Mini Jack	1 (for Power Source)		

Supplied accessories

- Power Cable: 4.5m
- USB Cable: 5m x 2, 1.8m x 1
- Remote Control: Compact Type
- Battery: Alkaline AA Battery x 2
- Setting Plate (Wall Mount)
- Wireless LAN Unit: ELPAP07
- External Control Pad
- Interactive Pen x 2
- Pen Tray
- Bundled Software: Epson Projector Software (CD-ROM)
- Password Protect Sticker
- User's Manual Set: CD-ROM

Optional accessories

- Spare Lamp: ELPLP71
- Air Filter: ELPAF40
- Quick Wireless Connection USB Key: ELPAP09
- Easy Interactive Pen 1: ELPPN03A
- Easy Interactive Pen 2: ELPPN03B
- Replacement Pen Tip: ELPPS01
- Table Projection Mount: ELPMB29
- Ceiling Mount: ELPMB23

EB-1400Wi/EB-1410Wi



*1 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

**2 Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

*3 When used in the general office environment (the amount of floating dust: 0.04-0.2 mg/m3). Based on the Epson's in-house test results.

*4 Selected Linux distribution only

© 2013 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

EPSON INDIA PVT. LTD.
12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008.
Tel: 080-30515000 Fax: 080-30515005

Regional Offices:
Ahmedabad - 26407176/77, Chennai - 30277500/11, Cochin - 4012315,
Coimbatore - 4393379, Indore - 4701830, Kolkata - 22831590, Mumbai -
28261515-17, New Delhi - 46585444, Pune - 30286000, Secunderabad - 40359898

Dealer's Stamp



Epson Helpline:
For product info or service - 1800 425 0011
For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)

www.epson.co.in



Official Partner
of Manchester United